

RETAIL Price List - Valid From May 2016

AV Products

Features	Retail Ex VAT	Retail Inc VAT
<p>BD32 MK II High performance multi-format/multi-channel player High performance 4K ready multi-format/multi-channel player Blu-ray, DVD, CD, SACD, DVD-A, DSD and media Dual simultaneous HDMI 1.4a outputs (3D) Proprietary Primare audio stage Multiple custom-engineered power supplies OLED user interface Analogue outputs: 1 pair Stereo XLR (4.4Vrms) and 1 pair RCA (2.2Vrms); 1 multichannel 7.1 RCA Digital outputs: 1x SPDIF (RCA); 1x optical (TOS-link); 2x HDMI Connections: HDMI input, 2 x USB-A, LAN, IR in/out 3.5 mm; RS232; Trigger in/out 3.5 mm D/A converter: Crystal DSD DAC CS439</p>	£ 2,916.67	£ 3,500.00
		
<p>SP33 HD 4K AV Preamplifier HD Video pass through (3D) Upscaling to 1080p 5 HDMI in 2 HDMI out New onscreen menu Individual offset per input Individual video settings per HDMI output</p>	£ 3,541.67	£ 4,250.00
		
<p>SP33 HD</p>	£ 2,916.67	£ 3,500.00
<p>SPA23 HD 4K AV Amplifier HD Video pass through (3D) Upscaling to 1080p 5 HDMI in 2 HDMI out New onscreen menu Individual offset per input Individual video settings per HDMI output 5 x 120W UFPD amplifiers</p>	£ 3,125.00	£ 3,750.00
		
<p>SPA23 HD</p>	£ 2,500.00	£ 3,000.00

RETAIL Price List - Valid From May 2016

Features	Retail Ex VAT	Retail Inc VAT
A30.7 Multi-Channel Power Amplifier High Current seven-channel UFPD Power Amplifier 7 x 150 W Per Channel (8 Ohms all channels driven) Fully independent power supplies Inputs: 7x RCA / 7x XLR switchable, RS232, trigger (12V) Available in Black or Titanium Finishes	£ 2,166.67	£ 2,600.00



AV Upgrade Boards		
HD Video for SP22 SPA22	£ 500.00	£ 600.00
HD Audio & Video for SPA22/SP32	£ 833.33	£ 1,000.00
HD Audio & Video & 4kVM upgrade for SPA22/SP32	£ 1,250.00	£ 1,500.00
4KVM Video upgrade for SPA23 & SP33	£ 791.67	£ 950.00

60 Series		
PRE 60 Reference Audiophile Dual-mono Pre-amplifier Integrated DAC/media board offers MEDIA/ streaming connections such as USB, iPod, LAN etc. at up to 24 bit/192 kHz, as well as Internet radio content, and also a digital audio input from a range of devices including CD players, smart phones, personal players, sat boxes etc. Analogue Inputs 2 pair XLR (L & R) 4 pair RCA (L & R) Other In/outputs RS232, IR in/out, Trigger in/out, RF Analogue Record Output 1 pair RCA (L & R) Pre Output 2 pair RCA (L & R), 2 pair XLR (L & R) Frequency Response 20Hz – 100kHz -3dB; THD + N < 0.003%, 20Hz – 100kHz, 0dB gain Signal to Noise -115 dBV Dimensions (W x D x H): 430 mm x 385 mm x 14.2 mm Available in Black or Titanium Finishes	£ 5,416.67	£ 6,500.00



RETAIL Price List - Valid From May 2016

Features	Retail Ex VAT	Retail Inc VAT
<p>A60 Reference audiophile, fully balanced UFPD stereo power amplifier Output power: 2x250W 8 Ohm (Both channels driven); 2x500W 4 Ohm THD+N: <0.02% (1kHz 250W 8 Ohm); <0.002 (10W 8 Ohm) Signal to Noise: 20-20kHz unweighted -105dBV Gain: 26dB Unbalanced, 20dB balanced Dimensions (W x D x H): 430 mm x 385 mm x 14.2 mm</p>	£ 5,416.67	£ 6,500.00



2 - Channel Products

<p>CD32 Reference CD Player D/A converter: 2x PCM1704, DF1706 (digital filter), 24/96 kHz Analogue outputs discrete analogue output stage: 1 pair RCA, 2.1 Vrms 1 pair XLR, 4.1 Vrms Output impedance: RCA 390 Ohm; XLR 47 Ohm Digital outputs: 1x SPdif (RCA); 1x AES/EBU (XLR); 1x optical (TOS-link) Frequency response: 20Hz – 20 kHz -0.5dB Available in Black or Titanium Finishes</p>	£ 1,666.67	£ 2,000.00
---	------------	------------



<p>CD22 CD Player D/A converter 1 x PCM1792, 24/192 kHz Sample frequency: 44.1 kHz, 48 kHz, 96 kHz and 192kHz The CD22 will play MP3/WMA files from disc or USB stick. Inputs: USB interface, IR input 3.5mm, RS232, Trigger in 3.5mm Outputs: unbalanced RCA, SPDIF, TOSlink, RS232C, IR, trigger Dimensions (W x D x H) 430 mm x 375 mm x 106 mm Colour options Black or Titanium</p>	£ 833.33	£ 1,000.00
---	----------	------------



RETAIL Price List - Valid From May 2016

Features	Retail Ex VAT	Retail Inc VAT
<p>MM30 Media Board Adapts the EISA award-winning I32 and PRE32 for audiophile streaming, internet radio and gapless audio playback. Genuine 24/192 DAC board 1 Coax input at 192kHz; 3 Toslink inputs at 192kHz 1 asynchronous USB-B input allowing playback of 192kHz audio from a computer 1 asynchronous USB-A input, allowing the device to play audio from USB/Iphone 1 Coax output transmitting at 192 kHz. Always connected to the active input source</p>	<p>£ 1,083.33</p>	<p>£ 1,300.00</p>
<p>I32 Audiophile Integrated Amplifier Output Power: 2 x 120 W at 8 Ohms 2 x 230 W at 4 Ohms Analogue Inputs: 2 pair XLR (L & R) 3 pair RCA (L & R) Analogue Record Output: 1 pair RCA (L & R) Pre Out : 1 pair RCA (L & R) Frequency Response: 10Hz – 20kHz, -0.5dB THD + N: < 0.05%, 20Hz – 20kHz, 10W at 8ohm Signal to Noise: -100 dBv Dimensions (W x D x H): 430 mm x 420 mm x106 mm</p>	<p>£ 1,666.67</p>	<p>£ 2,000.00</p>
<p>I32 with MM30 Media Board</p>	<p>£ 2,708.33</p>	<p>£ 3,250.00</p>
<p>I22 Audiophile Integrated Amplifier Output Power 2 x 80W at 8 Ohms, 2 x 160 W at 4 Ohms Analogue Inputs 4 x RCA (L & R) Analogue Outputs: Record, Pre Out RCA (L & R) Optional DAC Board: USB-B, TOSLINK, Coaxial inputs Dimensions (W x D x H) 430 mm x 420 mm x 106 mm</p>	<p>£ 833.33</p>	<p>£ 1,000.00</p>
<p>I22 with DAC Audiophile Integrated Amplifier with DAC Output Power 2 x 80W at 8 Ohms, 2 x 160W at 4 Ohms Analogue Inputs 4 x RCA (L & R) Analogue Outputs: Record, Pre Out RCA (L & R) DAC Board: USB-B, TOSLINK, Coaxial inputs Dimensions (W x D x H) 430 mm x 420 mm x 106 mm</p>	<p>£ 1,208.33</p>	<p>£ 1,450.00</p>
<p>I22 - Optional DAC Board</p>	<p>£ 375.00</p>	<p>£ 450.00</p>



RETAIL Price List - Valid From May 2016

Features	Retail Ex VAT	Retail Inc VAT
<p>PRE 32 Fully Balanced Preamplifier Analogue Inputs 2 pair XLR (L & R) 4 pair RCA (L & R) Other In/outputs RS232, IR in/out, Trigger in/out, RF. Optional MM30 media streaming module Dimensions (W x D x H): 430 mm x 385 mm x 105 mm</p>	<p>£ 1,458.33</p>	<p>£ 1,750.00</p>
<p>PRE32 with MM30 Media Board</p>	<p>£ 2,500.00</p>	<p>£ 3,000.00</p>
<p>DAC 30 Fully Balanced High Performance 24bit/192kHz Stereo DAC Crystal DSD DAC CS4398 (BD32) Fully balanced analogue output stage (BD32) Outputs: 1 pair XLR and 1 pair RCA (both 4,3V) Inputs: 1x asynchronous USB-B, 1x AES/EBU, 3x Optical, 3x Coax S/PDIF An audiophile relay controlled MUTE circuit Fully Linear PLS (R-Core) Signal to Noise 120dB Dimensions (W x D x H): 430 x 370 x 95mm</p>	<p>£ 1,666.67</p>	<p>£ 2,000.00</p>
<p>NP30 Network Player Audio formats: WAV, AIFF, FLAC, MP3, AAC, WMA, OGG, ALAC; Sample rates: 32-192kHz; Connections output: XLR, RCA, Digital (192 kHz), IRout, TRIGout; Connections input: 3 x optical, 1 x spdif, USB-A, USB-B, WLAN, LAN; Weight: 8.5 kg; Power consumption: Max 20 W; Standby: 0.5 W; Output impedance: RCA 100 Ohms; XLR 110 Ohms; XLR/RCA output: Both 2.2V; Signal to Noise: 120dB; Dimensions (W x D x H): 430 mm x 370 mm x 95 mm</p>	<p>£ 1,666.67</p>	<p>£ 2,000.00</p>
<p>aptX Bluetooth upgrade A high quality aptX Bluetooth upgrade for the PRE60 preamplifier, NP30 network player and the MM30 equipped network streaming versions of the I32 integrated amplifier and PRE32 pre-amplifier.</p>	<p>£ 150.00</p>	<p>£ 180.00</p>



RETAIL Price List - Valid From May 2016

Features	Retail Ex VAT	Retail Inc VAT
<p>A32 Dual Mono Power Amplifier Reference High Current Dual Mono Power Amplifier 2 x 250 W RMS (8 Ohms) - Both Channels Driven 2 x 400 W RMS (4 Ohms) - Both Channels Driven Dual Mono Construction Balanced & Unbalanced Inputs Dimensions with feet (W x D x H): 430 mm x 546 mm x 216 mm Available in Black or Titanium Finishes</p>	2,666.67	3,200.00
<p>A34.2 UFPD Power Amplifier Output power 2 x 150 W / 8 Ohm THD + N < 0.1% Bridged output power 1 x 550 W / 8 Ohms THD + N < 0.1% Inputs 2x RCA / 2x XLR switchable, RS232, trigger (12V) Dimensions (W x D x H): 430 mm x 385 mm x 105 mm Colour options Black or Titanium</p>	1,458.33	1,750.00
<p>R32 MM / MC Phono Stage Audiophile Dual-Mono Circuit Design R-core transformer High Quality Power Supplies Inputs: 1 pair RCA Outputs: 1 pair RCA Input impedance 10, 20, 50, 100, 200, 500 Ohms and 47 kOhms Output Impedance 100 Ohms Gain MM 41.5dB, MM with internal jumper 46.5dB, MC 62dB Available in Black or Titanium Finishes</p>	666.67	800.00
<p>C24 Remote Standard Primare system remote Improved design, feel and functionality Controls amplifiers, preamplifiers, CD players, BD players, DAC30, NP30 and surround processors</p>	£ 25.00	£ 30.00
<p>Zone 2 Remote</p>	£ 12.50	£ 15.00

